


NOTES:

1. WHEN CURB AND GUTTER IS NOT REQUIRED, THE RADIUS TO THE EDGE OF PAVEMENT SHALL NOT BE LESS THAN 40 FEET.
2. THE DISTANCE FROM THE RADIUS POINT TO THE CENTERLINE OF THE NEAREST INTERSECTION SHALL NOT BE LESS THAN 150 FEET.
3. CROWN GRADE SHALL BE 3% FOR ASPHALTED STREETS, AND BETWEEN 3% TO 5% FOR GRAVEL STREETS AS DETERMINED BY THE ENGINEER.
4. WHEN CURB, GUTTER AND SIDEWALK ARE CONSTRUCTED, THE RADIUS OF THE CUL-DE-SAC RIGHT OF WAY MAY BE REDUCED TO 50'.
5. UTILITY PEDESTALS AND ELECTRICAL TRANSFORMERS MAY REQUIRE EASEMENTS TO BE PLATTED BEYOND THE RIGHT OF WAY LINE.
6. CONSTRUCTION SPECIFICATIONS SHALL BE IN ACCORDANCE WITH STANDARD DETAILS.
7. TOTAL GRADE ACROSS THE CUL-DE-SAC IS NOT TO EXCEED 5%.

SCALE: NTS	DATE: 4/1/08	CITY AND BOROUGH OF JUNEAU, ALASKA LOCAL ACCESS STREET CUL-DE-SAC	
DRAWN BY: TAD	CHECKED BY: JB/STAFF		
APPROVED BY: 	REVISED: 8/14/2011	STANDARD 107	