



NOTES:

1. SIGN PANEL MATERIAL AND THICKNESS SHALL CONFORM TO MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES. SIGN SIZE AND PLACEMENT SHALL CONFORM TO MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES AND THE ALASKA SUPPLEMENT (SEE LATEST EDITION.)
2. SIGN POST SHALL BE INSERTED INTO HOLDER A MINIMUM OF 0'-6" AND A MAXIMUM OF 1'-0".
3. STREET NAMES SHALL BE ON 6" EXTRUDED SIGN PANELS.
4. STREET SIGN PANELS SHALL BE BETWEEN 12 AND 36 INCHES IN LENGTH AND IN 6" INCREMENTS.
5. STREET NAME LETTERING SHALL BE 3 INCHES HIGH, SERIES C TYPE.
6. THE BRACKETS FOR THE EXTRUDED STREET SIGN PANELS SHALL HAVE A MINIMUM SPAN OF 5 INCHES.
7. A STREET NAME ASSEMBLY SHALL BE INSTALLED ON EACH STOP SIGN AND WILL SHOW THE STREET NAMES OF BOTH INTERSECTING STREETS.
8. SNUGLY COVER TOP OF POST WITH EXTRUDED TELES PAR POST CAP.
9. WIND WASHERS ARE REQUIRED ON FRONT SIDE OF SIGNS. THEY SHALL BE 2" DIA STAINLESS FENDER WASHERS OR APPROVED EQUAL AND MATCH THE COLOR OF THE SIGN.

SCALE: NTS	DATE: 12/6/96	CITY AND BOROUGH OF JUNEAU, ALASKA	
DRAWN BY: DRW	CHECKED BY: JB/STAFF	SIGN ASSEMBLY SINGLE-POST	
APPROVED BY: <i>DRW</i>	REVISED: 8/14/2011	STANDARD 127A	