



MANHOLE LID
ABOVE GRADE

MANHOLE HEIGHTS ABOVE GRADE	
LOCATION OF MANHOLE	HEIGHT (H)
UNDEVELOPED & SWAMPY AREAS	12" TO 24"
HIGHWAY R.O.W.'S OUTSIDE OF TRAFFIC AREAS	1" TO 6"

MANHOLE LID
BELOW GRADE

MANHOLE DEPTHS BELOW GRADE	
LOCATION OF MANHOLE	DEPTH (D)
PAVED STREETS (SEE NOTE 1)	3/8" - 3/4"
BACKYARDS, GRAVEL STREETS, AND TRAVELED ALLEY AREAS	6" MAX

NOTES:

1. MANHOLE LID MUST CONFORM TO THE GRADE AND CROSS SLOPE OF THE STREET. SEE STANDARD 126.
2. MEASUREMENT SHALL BE TAKEN FROM THE TOP OF THE FRAME. SEE STANDARD 206A/206B
3. FOR BACKYARDS, GRAVEL STREETS AND TRAVELED ALLEY AREAS, BACKFILL TO MATCH EXISTING GRADE.
4. SANITARY SEWER MAIN CLEANOUT ELEVATIONS SHALL CONFORM TO THIS STANDARD.

SCALE: NTS	DATE: 12/2/96	CITY AND BOROUGH OF JUNEAU, ALASKA	
DRAWN BY: DRW	CHECKED BY: STAFF	MANHOLE HEIGHTS	
APPROVED BY: <i>DRW</i>	REVISED: 8/14/2011	STANDARD 205	