



ADDENDUM TO THE CONTRACT

for the

Area Wide Street Surfacing Improvements

Contract No. E13-255

ADDENDUM NO.: ONE

CURRENT DEADLINE FOR BIDS:
May 8, 2013

PREVIOUS ADDENDA: NONE

ISSUED BY: City and Borough of Juneau
ENGINEERING DEPARTMENT
155 South Seward Street
Juneau, Alaska 99801

DATE ADDENDUM ISSUED: May 2, 2013

The following items of the contract are modified as herein indicated. All other items remain the same. This addendum has been issued and is posted online. Please refer to the CBJ Engineering Contracts Division webpage at: <http://www.juneau.org/engineeringftp/contracts/Contracts.php>

SPECIAL PROVISIONS:

- Item No. 1: SECTION 02804 – BITUMINOUS SURFACE TREATMENT, PART 3 – EXECUTION, 3.2 EQUIPMENT, C. Aggregate Spreader, ***delete and replace*** Paragraph 1. ***in its entirety*** with the following paragraph:
1. The aggregate spreader shall be self-propelled and supported by at least four tires on two axles capable of providing a uniform application rate of aggregate from five to fifty pounds per square yard over a variable width up to 15 feet in a single pass. The uniformity of this machine shall not vary by more than one pound per square yard. The aggregate spreader shall be equipped with the means of applying the cover coat material to the surface with application controls so that the required amount of material will be deposited uniformly over the full width of the bituminous material.
- Item No. 2: SECTION 02804 – BITUMINOUS SURFACE TREATMENT, PART 3 – EXECUTION, 3.2 EQUIPMENT, D. Rollers, ***delete and replace*** Paragraph 1. ***in its entirety*** with the following paragraph:
1. A minimum of two self-propelled pneumatic tired rollers shall be used on the project unless otherwise requested by the Engineer. The rubber tired rollers shall have a gross load adjustable to apply 200 – 250 pounds per inch of rolling width. Tire pressure shall be specified for the pneumatic tire rollers and shall not vary more than plus or minus 5.0 psi. Depending on the speed of the Chip Seal operation and the width of coverage, additional rollers may be required.

By: 
Jennifer Mannix,
Contract Administrator