Ordinance 2021-35 – Exhibit B

CHAPTER 49.25 – ARTICLE IV. DIMENSIONAL STANDARDS

Table 49.25.400 Table of Dimensional Standards

•••

Zoning Regulations		RR	D-1	D-3	D-5	D-10 SF	D-10	D-15	D-18	MU	MU2	<u>MU3</u>	NC	LC	GC	WC	WI	I
Minimum Lot Size ¹																		
	ermissible ses	36,000	36,000	12,000	7,000	3,600 ¹⁰	6,000	5,000	5,000	4,000	4,000	<u>3,000</u>	<u>3,000</u>	2,000	2,000	2,000	2,000	2,000
	Bungalow ⁹		18,000	6,000	3,500	2,500	3,000	3,000	2,500									
	Duplex	54,000	54,000	18,000	10,500													
	Common Wall Dwelling				7,000	3,600 ¹⁰	5,000	3,500	2,500		2,500							
	Single- family detached, two dwellings per lot	72,000	72,000	24,000														
Minimum lot width		150'	150′	100′	70'	40'	50'	50′	50′	50′	50′	<u>40'</u>	<u>40'</u>	20'	20′	20′	20′	20′
Bungalow ⁹			75′	50'	35′	25'	25'	25′	25′									

Zoning Regulations	RR	D-1	D-3	D-5	D-10 SF	D-10	D-15	D-18	MU	MU2	<u>MU3</u>	<u>NC</u>	LC	GC	WC	WI	Ι
Common wall dwelling				60'	40'	40'	30'	20'		20′							
Minimum lot depth	150'	150'	100'	85'	85′ ¹⁰	85'	80'	80'	80′	80′	<u>None</u>	None	80'	60′	60'	60'	60'
Maximum lot coverage																	
Permissible uses	10%	10%	35%	50%	50%	50%	50%	50%	None	80%	<u>75%</u>	None	None	None	None	None	None
Conditional uses	20%	20%	35%	50%	50%	50%	50%	50%	None	80%			None	None	None	None	None
Maximum height permissible uses	45'	35′	35′	35′	35′	35'	35′	35'	None	45′ ⁴	<u>35'</u>	<u>35'</u>	45'	55′	35′4	45′ ⁴	None
Accessory	45′	25′	25′	25′	25′	25'	25′	25′	None	35′	<u>25'</u>	<u>25′</u>	<mark>35′</mark>	45′	35′ ⁴	45′ ⁴	None
Bungalow ⁹		25′	25′	25′	25′	25′	25′	25′									
Minimum front yard setback ³	25'	25′	25′	20'	20′ ¹⁰	20'	20′	20'	0'	5′ ^{5,8}	<u>0'</u>	<u>O'</u>	25'	10′	10′	10′	10′
<u>Maximum front</u> <u>yard setback</u>											20'	<u>15'</u>					
Minimum street side yard setback	17′	17′	17′	13'	10'	13'	13′	13′	0′	5′	<u>0'</u>	<u>0′</u>	17'	10′	10′	10′	10′

Zoning	RR	D-1	D-3	D-5	D-10 SF	D-10	D-15	D-18	MU	MU2	<u>MU3</u>	<u>NC</u>	LC	GC	WC	WI	1
Regulations																	

Maximum street side yard setback											<u>15'</u>	<u>10'</u>					
Minimum rear yard setback ³	25′ ²	25′	25′	20'	10′	20'	15′	10′	0′	5′	<u>5'</u>	<u>0'11</u>	10'	10′	10′	10′	10′
Minimum side yard setback ³	15'2	15′	10′	5′	3'	5'	5′	5′	0′	5′	<u>0'</u>	<u>0′11</u>	10'	10′	10′	10′	0′
Common wall dwelling				10′ ⁶	3'	5'7	5′ ⁷	5′ ⁷		5' ⁷							

Notes:

- 1. Minimum lot size is existing lot or area shown on chart in square feet.
- 2. Sixty feet between nonresidential and designated or actual residential site; 80 feet between industrial, extractive and other uses.
- 3. Where one district abuts another the greater of the two setbacks is required for both uses on the common property line.
- 4. (Height Bonus) Reserved.
- 5. (Pedestrian Amenities Bonus) Reserved.
- 6. Zero-foot setback for the portion of the dwelling with a common wall, five-foot setback or five-foot wide easement for the portion of the dwelling at the common lot line without a common wall, and ten-foot setback for the remaining side yards of the lot.
- 7. Zero-foot setback for the portion of the dwelling with a common wall, five-foot setback or five-foot wide easement for the portion of the dwelling at the common lot line without a common wall, and five-foot setback for the remaining side yards of the lot.
- 8. On corner lots, buildings shall be set back 15 feet from a street intersection. The area in which buildings shall be prohibited shall be determined by extending the edge of the traveled ways to a point of intersection, then measuring back 15 feet, then connecting the points.
- 9. Special restrictions apply to construction on bungalow lots. See special use provisions 49.65.600.
- 10. For lots adjacent to an alley, the following reductions to the dimensional standards apply:
 - (a) Minimal lot area includes 50% of adjacent alley (see graphic).
 - (b) Minimal lot depth includes 50% of the width of adjacent alley.
 - (c) Minimum front yard setback of ten feet.
- 11. Additional setbacks apply when lot abuts a multi-family or single-family residential zoning district.